



KONVOX ROUNDSLING 1 TONNE

GENERAL INFORMATION

The KONVOX roundsling is the ideal choice for demanding lifting tasks. This 1 tonne (1,000kg) roundsling offers strength and flexibility in one. Thanks to TÜV certification, you can rely on maximum safety and durability and can be checked on the sewn-in blue label.

AVAILABILITY

Dimensions	Article number	EAN code
Konvox Roundsling 1 tonne 0,5m purple	LAZE1400-1779	8717568991306
Konvox Roundsling 1 tonne 1m purple	LAZE1400-1783	8717568991313
Konvox Roundsling 1 tonne 1,5m purple	LAZE1400-1789	8717568991320
Konvox Roundsling 1 tonne 2m purple	LAZE1400-1793	8717568991337

TECHNICAL SPECIFICATIONS

Feature	Specifications
Material (strap & core)	PES (polyester)
Length of strap in m ¹	0.5, 1, 1.5, 2
Width of strap in mm	45
Thickness of strap in mm	4
WLL (Working Load Limit) in Tons - straight	1
WLL (Working Load Limit) in Tons - U-loop	2
WLL (Working Load Limit) in Tons - loop	0.8
WLL (Working Load Limit) in Tons - 0° - 45° angle	1.4
WLL (Working Load Limit) in Tons - 45° - 90° angle	1
Strap Colour	Purple
Weight in kg	0,18, 0.31, 0.44, 0.58
SF (Safety Factor)	7:1
Attachment points	None
Breaking force (kN)	70
Standardisation (produced according to)	EN1492-2
TÜV- certified	Yes

Visit our website for technical information: www.berdal.com/downloads

MEMBER OF THE BERDAL FAMILY

SAFETY AND USE OPTIONS

Always inspect and check the roundsling (visually) for wear, discolouration and burn marks before use. Never use over sharp edges without corner protection. Make sure there are no knots or twists in the strap. Rejection criteria include: damaged or missing label, (in) torn or damaged sleeve or core. Only use in straight hoist, U-loop or loop. Store in dry, clean place out of direct sunlight and away from aggressive chemicals.

APPLICATION

A roundsling can be used for lifting and moving loads. For example, in construction, industry and logistics. Its use depends on the nature of the load, the method of lifting, and safety requirements.

HOW TO USE

You place the roundsling around the object and then pull one end through the loop of the other end of the sling, creating a sturdy and safe lifting construction. No persons should be under the load, use only smoothly rounded hooks with a proper radius. If friction of the roundsling is unavoidable, use wear sleeves. Make sure the lifting point is above the centre of gravity of the load to ensure balanced lifting. Otherwise, the load may slip out of the round sling. Never use roundslings for a higher working load than indicated on the label. Never move the load to be hoisted within the roundsling. In addition, avoid dragging the sling over the ground or rough surfaces.

WLL 1000 kg SF 7	
2000kg 	800kg 
0° - 45° 	45° - 60° 
1400kg	1000kg

